

WALLMax[®]

Panel Wall Fencing



10 Year Warranty*



Termite Proof



Easy Maintenance



Strength & Durability



Noise Reduction



Insulated No Heat Transfer



Economical Compared To Masonry Walls



Asbestos Free



Head Office/Manufacturing 44 Preston Street PENRITH NSW ☎ 02 4731 6974

ALBION PARK (02) 4257 5977 BROOKVALE (02) 9907 1007 CARDIFF (02) 4956 9460 DUBBO (02) 6882 6434 MINCHINBURY (02) 9675 2822 NOWRA (02) 4421 3301 QUEANBEYAN (02) 6284 2688 SMEATON GRANGE (02) 4647 2507 WEST GOSFORD (02) 4324 4122 ROCKLEA QLD (07) 3275 3700

www.dunnandfarrugia.com.au

WALLMax®

Panel Wall Fencing

WALLMax® Panel Wall Fencing is suitable for both residential and commercial application, a modular fibre cement infill panel set between large pillar style posts with capping, fabricated from strong corrosion resistant aluminium. Being both sturdy and stylish this wall also offers a unique sound barrier between neighbours or commercial situations. The panels can be finished with a variety of coatings and unlimited colours.

A masonry appearance wall is achieved with no footings required.

WALLMax® offers prestige styling, privacy and a very cost effective solution for sound control.

Painting/Coating required

WALLMax® will easily withstand the weather uncoated for many years. However we do recommend that the wall is coated within 30 days of installation. This is also a condition of our warranty.

The panels must be primer coated while dry, immediately after installation. The panel strength is lowered and the painted finish could be compromised should the wall become wet prior to sealing, the posts and capping are pre coated Merino/Terrace®. An elegant finished surface can be achieved by applying either a smooth or textured exterior coating. Textures ranging from smooth, simulating the modern rendered look, to a heavy bold surface are appealing.

WHY CHOOSE WALLMax®?

- No masonry cracks – allows for ground movement
- Lightweight product – no heavy, dangerous tilting
- DIY system – very simple to install
- No strip footings – low cost, no mess, no hassle
- Economical – compared to masonry & concrete walls
- Very sturdy – avoid rotting, warping, dents & corrosion
- Quiet – superior noise reduction up to 20+dB
- Insulated – cool, no heat transfer
- Easy to coat – smooth wall surface, pre-primed posts
- Modular – design and build your own style
- Can include decorative powdercoated or TimberSLAT™ Louvres. Fixed or adjustable.
- Combat the elements – fire and termite resistant
- Transport efficient – lightweight components



SPECIFICATIONS

Panels

Panel sizes available: 2400mm wide x 1200, 1500, 1800, 2100, or 2400mm high (doesn't include post width)
The panels are fibre cement board 50mm thick and up to 2400mm high. Asbestos free, fire rated and CE compliant.....

Posts

Post sizes available: 2.5mm thick x 150mm square
The posts are extremely strong due to their aluminium extruded design with a thickness of 2.5mm. Each 150mm square. Both posts and capping are pre painted Merino/Terrace®.
Size and depth of hole required: 1800mm to 2100mm high panels require posts to be 900mm in ground with 400mm diameter hole. 2400mm high panels require posts to be 1000mm in ground with 400mm diameter hole.


DESIGN YOUR FENCE....



Solid Wall



Insert TimberSLAT™



Insert LouvrLAT®/SlatLAT™ & Letterbox



Insert Tubular

